

MODEL: SHUTTLE™ 6 72V

TYPE: ELECTRIC POWERED PERSONNEL CARRIER

MODEL YEAR: 2019 Part No:. 670623G01

PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Solid State continuously variable seperately excited speed controller
- Dash mounted direction selector switch (Forward-Neutral-Reverse)
- Anti-roll back, walkaway braking and alarm
- Anti-stall motor protection
- Regenerative 'Pedal Down' and/or 'Pedal Up' braking

- Six, 12 Volt Deep Cycle
- Full torque, reduced speed reverse
- Inductive throttle sensor
- Diagnostic indicator
- Factory selectable performance options

Battery Charger: 72 VDC. H120/230 VAC 50/60 Hz. Underwriters Laboratories (U.L.) Listed, (C.S.A. Certified)

Motor: 72 Volt AC Induction, solid copper windings. Non vented 22.4 hp (16.7 kW) Peak

Dash Mounted Forward-Neutral-Reverse

Drive Train: Direct motor shaft connected to transaxle pinion shaft Electrical System: 72 Volt DC, Six, 12 volt deep cycle storage batteries

Transaxle: Differential with helical gears

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating sytsem.

PRODUCT OVERVIEW

Regenerative braking.

17:1

Dimensions		Performance		
Overall Length	136.0 in (345 cm)	Seating Capacity	6 Person	
Overall Width	48.5 in (123 cm)	Dry Weight	964 lb (437 kg) (Without Batteries)	
Overall Height (No Canopy)	48.6 in (123 cm) (Top of steering wheel)	Curb Weight	1456 lb (660 kg)	
Overall Height (With Canopy)	72.0 in (183 cm)	Vehicle load capacity	1200 lb (544 kg)	
Wheel Base	93.5 in (237 cm)	Outside Clearance Circle	25.5 ft (7.8 m)	
Front Wheel Track	34.2 in (86.7 cm)	High Speed (Level Grnd)	$16.5 \text{ mph} \pm 0.5 \text{ mph} (26.4 \text{ kph} \pm 0.8 \text{ kph})$	
Rear Wheel Track	38.0 in (97 cm)	Low Speed (Level Grnd)	12 mph \pm 0.5 mph (19.3 kph \pm 0.8 kph)	
Gnd Clearance @ Differential	4.3 in (11 cm)	Towing Capacity	N/A	
Vehicle Power		Steering & Suspension		
Power Source	72 Volts DC	Steering	Self-compensating rack and pinion	
Motor Type	AC Induction	Front Suspension	Leaf springs with hydraulic shock absorbers	
Intermittent Horsepower (kW)	22.4 hp (16.7 kW) Peak	Rear Suspension	Leaf springs with hydraulic shock absorbers	
Electrical System	72 Volt	Service Brake	Rear wheel mechanical self-adjusting drum	
Batteries (Qty, Type)	Six, 12 Volt Deep Cycle		Regenerative braking	
Key or Pedal Start	Pedal Start	Parking Brake	Self-compensating, single point engagement	
Battery Charger	72 VDC, 120/230 VAC, UL & CSA	Front Tires	Hole-N-One 18 x 8.50 - 8 (4 Ply Rated)	
Speed Controller	350 Amp AC	Rear Tires	Hole-N-One 18 x 8.50 - 8 (4 Ply Rated)	
Drive Train	Motor Shaft Direct Drive	Body & Chassis		
Transaxle	Differential with helical gears	Frame	Welded steel. DuraShield™ powder coat	

Gear Selection

Rear Axle Ratio

Body & Finish

Standard Color

Seat Pod

Injection molded TPO

Thermoform ABS

Ivory



OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

lk oue	Ctd Ont F	14
Item	Std Opt F	Ia
TIRES & WHEELS: Front:		
Hole-N-One 18x8.5 - 8 (4 Ply)		
USA Trail 18x8.5 - 8 (Load Rance C/6 Ply) (Set of Two) Rear:	•	
Hole-N-One 18x8.5 - 8 (4 Ply) USA Trail 18x8.5 - 8 (Load Rance C/6 Ply) (Set of Two)		
Wheel Covers:	•	
Silver Metallic (Set of 4)		
Gold Metallic (Set of 4) COLORS:		
Body Color - Ivory Body Color - Forest Green		
Body Color - Black		
Body Color - Bright White		
Body Color - Electric Blue		
Body Color - Flame Red		
Premium:		
Body Color - Orange		
Body Color - Almond		
Body Color - Safety Yellow		
Body Color - Platinum		
Body Color - Metallic Charcoal		
Body Color - Patriot Blue		
SEATING:		
Seat Color 6 Passenger Only (Oyster)		
Seat Color 6 Passenger Only (Tan)		
Seat Color 6 Passenger Only (Gray)		
OTHER ENHANCEMENTS:		
Brushguard		
Front Hydraulic Disc Brakes		
TRANSAXLE:		
Limited Slip Differential	•	

Item	Std	Opt	Fld
ELECTRICAL:			
Brake Lights		•	
Horn Switch			
Hour Meter, Hour, SOC, Grn Back Lit			
Port, USB, Dual, 12V Input			
Speed Switch, 2 POS (Rabbit/Turtle)			
DC/DC Converter, Isolated, 72V			
L.E.D. Headlights		•	
Turn Signals with 4-Way Flashers		•	
Unique Group Key Switch		•	
OTHER ENHANCEMENTS:			
Glove Box Door, LH/RH		•	
Glove Box Door, LH		•	
Glove Box Door, RH		•	
BATTERY:			
T1275 Plus Batteries (12V)			
T1275 Hydrolink (12V)		•	
Battery Fill Hand Pump			•
Battery Fill System Nozzle, 20' Hose			•
BATTERY CHARGER:			
Charger, 72V, 1000W, D Plug, Off BD	•		
Charger, 72V, 1500W On-Board, High Output		•	
Charger Cord - 5M (16ft) North American (For On-Board)		•	
OTHER ENHANCEMENTS:			
Rear View Mirror (Sun Canopy or Cab Required)			•
Mirror Assy (Sun Canopy or Cab Required)			•
Kit, Mirror 5 Panel (Sun Canopy or Cab Required)			•
WEATHER PROTECTION:			
Kit, Split W/Shield Shuttle 4/6			•
Windshield Kit, Flat-Clip on CLR			•
Sun Canopy 116" (295 cm) Top (Black)			•
Sun Canopy 116" (295 cm) Top (Beige)			•
Sun Canopy 116" (295 cm) Top (White)			•
Enclosure, White			•