

## HAULER® 1200

LOADED WITH RELENTLESS FUNCTIONALITY.

The new Hauler® 1200 is equipped to tackle the burden of every job, with a rugged truck-like design perfected by Superintendents. A large bed packed full of essential functionality can easily be converted for any task. Featuring tie down locations, divider slots and a full line of affordable accessories, transporting everything from sod to small equipment has never been easier. Your work is unforgiving, let the Hauler 1200 carry the load.

LET'S WORK.®

13.5HP KAWASAKI

1500LB

WASAKI TOW
GAS CAPACITY

12 CU FT CARGO BED **1200**LB

LOAD CAPACITY





## **CUSHMAN** HAULER® 1200









## OPTIONS & ACCESSORIES

- Limited Slip Differential
- Locking Glove BoxGlove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- LED Headlights Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- Fuel Gauge

POWER DUI	/IP	-
		-

- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

FRAME	Welded Steel with E-Shield™ e-coat plus DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO, Painted	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	119 in (302 cm)	
OVERALL WIDTH	49.4 in (125 cm)	
OVERALL HEIGHT W/CANOPY	71 in (179 cm)	
WHEEL BASE	76.8 in (195 cm)	
FRONT WHEEL TRACK	35 in (89 cm)	
REAR WHEEL TRACK	38.5 in (98 cm)	
GROUND CLEARANCE	3.5 in (9 cm)	
CARGO BOX CAPACITY	12 cu ft (0.34m^3)	
POWER		
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder	
VALVE TRAIN	Single Cylinder OHV	
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.	
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator	
BATTERY (QTY/TYPE)	One 12V Maintenance Free	
KEY OR PEDAL START	Pedal Start	
AIR CLEANER	Dry Cartridge	
LUBRICATION	Pressurized Oil System	
DIL FILTER	Spin-On	
COOLING SYSTEM	Air Cooled	
FUEL CAPACITY	6 Gallon (22.7 L) Tank	
DRIVE TRAIN	Continuously Variable Transmission (CVT)	
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Forward-Reverse	
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)	
PERFORMANCE		
SEATING CAPACITY	2 Person	
CURB WEIGHT	980 lb (445 kg)	
BED LOAD CAPACITY	800 lb (364 kg)	
VEHICLE LOAD CAPACITY	1200 lb (545 kg)	
SPEED	$14.5 \text{ mph} \pm 0.5 \text{ mph} (23.34 \text{ kph} \pm 0.8 \text{ kph})$	
TOWING CAPACITY	1500 lb (680 kg) max	
DUTSIDE CLEARANCE CIRCLE	21.5 ft (7.01 m)	
STEERING & SUSPE	NSION	
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TIRES	18 x 8.5-8	