

MODEL: SHUTTLE™ 4

**TYPE: GAS POWERED PERSONNEL CARRIER** 

**MODEL YEAR: 2017** 

Part No: 618851

Dimensions

Overall Length

Overall Width



Fixed float bowl with remote pulse fuel pump

Electronic spark/magneto

Replaceable dry cartridge

4 Person

### PRODUCT SPECIFICATION

#### **CONFIGURATION HIGHLIGHTS**

Fuel System:

Ignition:

Air Cleaner:

Engine: 13.5 hp (10.1 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

Valve Train: Overhead valve

Lubrication: Pressurized oil system, spin-on oil filter
 Balancer: Internal counter rotating balance shaft

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

**Drive Train:** Automatic, continuously variable transmission (CVT)

135.0 in (343 cm)

48.5 in (123 cm)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Single point park brake release with self-compensating system

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

#### **PRODUCT OVERVIEW**

Performance

Seating Capacity

Front & Rear Body & Finish

Seat Pod & Finish

Standard Color

Overall Height (No Canopy)	48.6 in (123 cm) (Top of steering wheel)
Overall Height (With Canopy)	72.0 in (183 cm)
Wheel Base	93.5 in (237 cm)
Front Wheel Track	34.2 in (86.7 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	4.3 in (11 cm)
Cargo Box Width (inside)	42.5 in (108 cm)
Cargo Box Length (inside)	32.0 in (80 cm)
Cargo Box Depth (inside)	11.5 in (29 cm)
Cargo Box Capacity	9 cu ft (.25 m3)
Cargo Box material	Wood Stake Sides
Vehicle Power	
Power Source	4 Cycle 24.5 cu in (401 cc). Low Emission
Valve Train	Single Cylinder OHV
Horsepower (kW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Battery (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Industrial Rated Dry Filter
Lubrication	Pressurized Oil System
Oil Filter	Spin-On
Cooling System	Air Cooled
Fuel Capacity	6.0 Gallon (22.7 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears

Forward - Reverse

11.42:1 (Forward) 15.78:1 (Reverse)

Dry Weight	896 lb (405 kg)
Curb Weight	936 lb (425 kg)
Bed Load Capacity	400 lb (180 kg)
Vehicle load capacity	1200 lb (545 kg)
Outside Clearance Circle	25.5 ft (7.8 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	16 mph $\pm$ 0.5 mph (26 kph $\pm$ 0.8 kph)
Towing Capacity	N/A
Steering & Suspension	
Steering	Self-compensating reduction rack and pinion
Steering Front Suspension	Self-compensating reduction rack and pinion Leaf springs with hydraulic shock absorbers
3	
Front Suspension	Leaf springs with hydraulic shock absorbers
Front Suspension Rear Suspension	Leaf springs with hydraulic shock absorbers Leaf springs with hydraulic shock absorbers
Front Suspension Rear Suspension Service Brake	Leaf springs with hydraulic shock absorbers Leaf springs with hydraulic shock absorbers Rear wheel mechanical self-adjusting drum
Front Suspension Rear Suspension Service Brake Parking Brake	Leaf springs with hydraulic shock absorbers Leaf springs with hydraulic shock absorbers Rear wheel mechanical self-adjusting drum Self-compensating, single point engagement
Front Suspension Rear Suspension Service Brake Parking Brake Front Tires	Leaf springs with hydraulic shock absorbers Leaf springs with hydraulic shock absorbers Rear wheel mechanical self-adjusting drum Self-compensating, single point engagement 18 x 8.50 - 8 (4 Ply Rated)

ABS, Painted

Patriot Blue

Injection molded TPO, Painted

Some items shown may be optional equipment

Gear Selection

Rear Axle Ratio



# OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)\*

Item	Std	Opt	Fld
TIRES & WHEELS:			
Front:			
18 x 8.50 - 8 (4 Ply Rated)	Χ		
Improved Surface 18 x 8.50 - 8 (Load Range C)		Χ	
Rear:			
18 x 8.50 - 8 (4 Ply Rated)	Χ		
Improved Surface 18 x 8.50 - 8 (Load Range C)		Χ	
Wheel Covers:			
Spoke, Gold		Χ	
Spoke, Silver		Χ	

#### Item ELECTRICAL: **Head Lights** Horn Χ Fuel Gauge Low Oil Indicator Χ Individual Key Switch Χ Unique Group Key Switch Χ Brake Lights Χ Hour Meter LED Headlights Χ Turn Signals with 4-Way Flashers

### **COLORS:**

Body Color - Patriot Blue	Χ		
Body Color - Forest Green		Χ	
Body Color - Ivory		Χ	
Body Color - Safety Yellow		Χ	
Body Color - Black		Χ	
Body Color - Inferno Red		Χ	
Body Color - Bright White		Χ	
Body Color - Flame Red		Χ	
Body Color - Platinum		Χ	
Body Color - Burgundy		Χ	
Body Color - Almond		Χ	
Body Color - Electric Blue		Χ	
Body Color - Steel Blue		Χ	
Body Color - Metallic Charcoal		Χ	
Body Color - Sunburst Orange		Χ	
Body Color - British Racing Green		Χ	
Body Color- Monster Green		Χ	
Body Color- Barley Gold		Χ	
Body Color- Oasis Green		Χ	
Body Color- Java Brown		Χ	

### OTHER PERFORMANCE:

Cargo Bed	Χ		
Front Hydraulic Disc Brakes		Χ	
CE Kit		Χ	
Fender Flare	Χ		
Brush Guard	Χ		

## Pin Stripes:

Pewter	Х	
Black	Х	
Silvor	V	

### TRANSAXLE:

Std. Jetting, 0-3K Ft	Χ		
High Altitude Jetting, 3-6K Ft		Χ	
High Altitude Jetting, 6-10K Ft		Χ	
Limited Slip Differential, Std Jetting		Χ	
Limited Slip Differential, 3-6K Ft Jetting		Χ	

Pewter	Χ	
Black	Χ	
Silver	Χ	

## **WEATHER PROTECTION:**

Sun Canopy 118 in (300 cm) (Beige)		Χ
Sun Canopy 118 in (300 cm) (White)		Χ
Sun Canopy 118 in (300 cm) (Black)		Χ
Windshield Flat		Χ
Windshield Fold Down		Χ
Rear View Mirror (Sun Canopy Required)		Χ

## Seating:

Seat Color - Oyster	Χ		
Seat Color - Gray		Χ	
Seat Color - Tan		Χ	
Custom Seat Color (upon request)		Χ	