



Models CRF110F
CRF110F

GENERAL

Warranty 3 months

Service Intervals 1000km

0 - 100 km/h (sec) -

DIMENSIONS AND WEIGHTS

Claimed KERB Weight 75

Length (mm) 1560

Width (mm) 686

Height (mm) 912

Seat height (mm) 660

Rake/Trail (°/mm) -

Wheel Base 1065

DRIVE

Drive Chain

Front Suspension 31mm fork, 100mm stroke, 90mm axle travel

Rear Suspension Mono shock, 59mm stroke

ENGINE

Tank Capacity (l) 5

Starter Electric / Primary kick

Engine Configuration Single cylinder four stroke

Cylinders 1

Valves per Cylinder 2

Capacity 109

Power (KW) -

Torque (NM) -

Gearbox 4 speed, with automatic clutch

SAFETY

Brakes "(f) 95mm Drum (r) 95mm Drum"

STYLING

Frame Material Steel backbone

WHEELS

Tyres Front 70/100-14

Tyres Rear 80/100-12

Wheels Wire spoke

STANDARD AVAILABLE ACCESSORIES

Luggage -

Maintenance -

Comfort -

Utility -

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of

whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.