



Models	CRF1100 Adventure Sports Adventure Sport DCT 20YM	CRF1100 Adventure Sports Adventure Sports ABS 20YM
GENERAL		
Warranty	2 yrs	2 yrs
Service Intervals	12000 km	12000 km
0 - 100 km/h (sec)	-	-
DIMENSIONS AND WEIGHTS		
Claimed KERB Weight	248	238
Length (mm)	2340	2340
Width (mm)	930	930
Height (mm)	1560	1560
Seat height (mm)	870/850mm (STD position / Low position)	870/850mm (STD position / Low position)
Rake/Trail (°/mm)	-	-
Wheel Base	1,575mm	1,575mm
DRIVE		
Drive	O-ring sealed chain	O-ring sealed chain
Front Suspension	EERATM - Showa Telescopic inverted fork with an inner tube diameter of 45mm, and Showa EERATM with compression and rebound dumping adjustments, 230mm stroke.	Show a 45mm cartridge-type inverted telescopic fork with dial-style preload adjuster and damping adjustment, 230mm stroke.
Rear Suspension	EERATM - Monoblock aluminium swing arm with Pro-Link with Showa gas-charged damper, hydraulic remote control preload adjuster and electric control unit with compression and rebound damping adjustments, 220 mm rear wheel travel	Monoblock aluminium swing arm with Pro-Link with Showa gas-charged damper, hydraulic dial-style preload adjuster and rebound damping adjustments, 220 mm rear wheel travel.
ENGINE		
Tank Capacity (l)	24.8 litres	24.8 litres
Starter	Electric	Electric
Engine Configuration	Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam	Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam
Cylinders	2	2
Valves per Cylinder	4 Valves per Cylinder	4 Valves per Cylinder
Capacity	1084cm ³	1084cm ³
Power (KW)	75kW @ 7,500rpm	75kW at 7,500rpm
Torque (NM)	105Nm at 6,250rpm	105Nm at 6,250rpm
Gearbox	6-speed DCT	Constant mesh 6-speed MT
SAFETY		
Brakes	Front: 310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads.	

Rear: 256mm wave hydraulic disc with single piston caliper and sintered metal pads. 2-channel with rear ABS OFF mode.

STYLING

Frame
Material

Semi double cradle

Semi double cradle

WHEELS

Tyres Front 90/90-21M/C 54H (tubeless type)
Bridgestone Battlax Adventurecross
Tourer AX41T Metzler Karoo Street

90/90-21M/C 54H (tubeless type) Bridgestone Battlax
Adventurecross Tourer AX41T
Metzler Karoo Street

Tyres Rear 150/70R18M/C 70H (tubeless type)
Bridgestone Battlax Adventurecross
Tourer AX41T Metzler Karoo Street

150/70R18M/C 70H (tubeless type) Bridgestone Battlax
Adventurecross Tourer AX41T
Metzler Karoo Street

Wheels Front: 21M/C x MT2.15 wire spoke with
aluminium rim. Rear: 18M/C x MT4.00 wire
spoke with aluminium rim

Front: 21M/C x MT2.15 wire
spoke with aluminium rim.
Rear: 18M/C x MT4.00 wire
spoke with aluminium rim

STANDARD AVAILABLE ACCESSORIES

Luggage

Connering Lights

Connering Lights

Maintenance

Apple Car Play Navigation

Apple Car Play Navigation

Comfort

Bluetooth Connectivity LCD Meter, TFT
6.5inch touch panel multi information
display

Bluetooth Connectivity LCD
Meter, TFT 6.5inch touch panel
multi information display

Utility

Daytime running lights, Bluetooth audio
and Apple Carplay, USB socket, auto turn
signal cancel, cruise control, emergency
stop signal, IMU, HSTC and wheelie control

Daytime running lights,
Bluetooth audio and Apple
Carplay, USB socket, auto turn
signal cancel, cruise control,
emergency stop signal, IMU,
HSTC and wheelie control)

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.