?	
Models	CRF450RX
	CRF450RX 21YM
GENERAL	
Warranty	None
Service Intervals	-
0 - 100 km/h (sec)	
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	116
Length (mm)	2175
Width (mm)	827
Height (mm)	1274
Seat height (mm)	960
Rake/Trail (°/mm)	-
Wheel Base	1485
DRIVE	
Drive	Chain
Front Suspension	Showa 49mm coil spring fork (305mm stroke)
Rear Suspension	Showa monoshock using Honda Pro-Link system (133 stroke, 3125mm axle travel
ENGINE	
Tank Capacity (l)	8.5
Starter	Electric
Engine Configuration	Liquid-cooled 4-stroke single cylinder uni-cam
Cylinders	1
Valves per Cylinder	4
Capacity	449
Power (KW)	
Torque (NM)	
Gearbox	5-spd
SAFETY	
Brakes	(F)260mm hydraulic wave disc. (R)240mm hydraulic wave disc
STYLING	
Frame Material	Aluminium twin tube
WHEELS	
Tumos Enont	00/00 01

Tyres Front90/90-21Tyres Rear140/80-18WheelsAluminium rim/wire spoke

## STANDARD AVAILABLE ACCESSORIES

-

\_

Luggage

Maintenance

Comfort

Utility

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.