



Models CRF250R
CRF250R

GENERAL

Warranty None
Service Intervals As per owners manual
0 - 100 km/h (sec) -

DIMENSIONS AND WEIGHTS

Claimed KERB Weight 108
Length (mm) 2183
Width (mm) 827
Height (mm) 1274
Seat height (mm) 957
Rake/Trail (°/mm) -
Wheel Base 1480

DRIVE

Drive Chain
Front Suspension 49mm Showa coil-sprung fork
Rear Suspension Showa monoshock using Honda Pro-Link system

ENGINE

Tank Capacity (l) 6.3
Starter Electric
Engine Configuration 4 stroke, single cylinder, uni-cam
Cylinders 1
Valves per Cylinder 4
Capacity 249
Power (KW) -
Torque (NM) -
Gearbox 5-spd

SAFETY

Brakes (f)260mm wave hydraulic disc with twin-piston calipers (r) 240mm wave Hydraulic Disc

STYLING

Frame Material Aluminium twin tube

WHEELS

Tyres Front 80/100-21 Dunlop Geomax
Tyres Rear 100/90-19 Dunlop Geomax
Wheels Aluminium rim/wire spoke

STANDARD AVAILABLE ACCESSORIES

Luggage -
Maintenance -
Comfort -
Utility -

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.