



Models	CRF1100 Africa Twin Africa Twin DCT 20YM	CRF1100 Africa Twin Africa Twin ABS 20YM
<b>GENERAL</b>		
Warranty	2 yrs	2 yrs
Service Intervals	12000 km	12000 km
0 - 100 km/h (sec)	-	-
<b>DIMENSIONS AND WEIGHTS</b>		
Claimed KERB Weight	236	226
Length (mm)	2330	2330
Width (mm)	960	960
Height (mm)	1395	1395
Seat height (mm)	870/850mm (STD position / Low position)	870/850 (STD position / Low position)
Rake/Trail (°/mm)	-	-
Wheel Base	1,575mm	1,575mm
<b>DRIVE</b>		
Drive	O-ring sealed chain	O-ring sealed chain
Front Suspension	Show a 45mm cartridge-type inverted telescopic fork with dial-style preload adjuster and DF adjustments, 230mm stroke	Show a 45mm cartridge-type inverted telescopic fork with dial-style preload adjuster and DF adjustments, 230mm stroke
Rear Suspension	Monoblock aluminium swing arm with Pro-Link with Showa gas-charged damper, hydraulic dial-style preload adjuster and rebound damping adjustments, 220 mm rear wheel travel	Monoblock aluminium swing arm with Pro-Link with Showa gas-charged damper, hydraulic dial-style preload adjuster and rebound damping adjustments, 220 mm rear wheel travel
<b>ENGINE</b>		
Tank Capacity (l)	18.8	18.8
Starter	Electric	Electric
Engine Configuration	Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam	Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam
Cylinders	2	2
Valves per Cylinder	4 Valves per Cylinder	4 Valves per Cylinder
Capacity	1084cm <sup>3</sup>	1084cm <sup>3</sup>
Power (KW)	75kW @ 7,500rpm	75kW at 7,500rpm
Torque (NM)	105Nm at 6,250rpm	105Nm @ 6,250rpm
Gearbox	6-speed DCT	Constant mesh 6-speed MT
<b>SAFETY</b>		
Brakes	Front: 310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads.	

Rear: 256mm wave hydraulic disc with single piston caliper and sintered metal pads. 2-channel with rear ABS OFF mode.

## STYLING

Frame Material	Semi double cradle	Semi double cradle
----------------	--------------------	--------------------

## WHEELS

Tyres Front	90/90-21M/C 54H (tube type)	90/90-21M/C 54H (tube type)
Tyres Rear	50/70R18M/C 70H (tube type)	150/70R18M/C 70H (tube type)
Wheels	Front: 21M/C x 2.15 wire spoke with aluminium rim. Rear: 18M/C x MT4.00 wire spoke with aluminium rim	Front: 21M/C x 2.15 wire spoke with aluminium rim. Rear: 18M/C x MT4.00 wire spoke with aluminium rim

## STANDARD AVAILABLE ACCESSORIES

Luggage	-	-
Maintenance	Apple Car Play Navigation	Apple Car Play Navigation
Comfort	Bluetooth Connectivity 'LCD Meter, TFT 6.5inch touch panel multi information display	'Bluetooth Connectivity LCD Meter, TFT 6.5inch touch panel multi information display
Utility	Daytime running lights, Bluetooth audio and Apple Carplay, USB socket, auto turn signal cancel, cruise control, emergency stop signal, IMU, HSTC and wheelie control)	Daytime running lights, Bluetooth audio and Apple Carplay, USB socket, auto turn signal cancel, cruise control, emergency stop signal, IMU, HSTC and wheelie control)

## DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.