



Models	TRX250TM TRX420FA6	TRX250TM TRX250TM (4X2)
GENERAL		
Warranty	6 months	6 months
Service Intervals	100 hours	100 hours
0 - 100 km/h (sec)	-	-
DIMENSIONS AND WEIGHTS		
Claimed KERB Weight	265	197
Length (mm)	2105	1905
Width (mm)	1203	1034
Height (mm)	1163	1069
Seat height (mm)	855	792.5
Rake/Trail (°/mm)	-	-
Wheel Base	1270	1130
DRIVE		
Drive	Shaft	Direct rear driveshaft
Front Suspension	Independent double-wishbone; 160mm inches travel	Independent double-wishbone; 13 cm. travel
Rear Suspension	Independent double-wishbone; 160mm inches travel	Swingarm with single shock; 124.5mm travel
ENGINE		
Tank Capacity (l)	13.3	9.1
Starter	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
Engine Configuration	Liquid-cooled OHV semi-dry-sump longitudinally mounted single-cylinder four-stroke	air-cooled OHV longitudinally mounted single-cylinder four-stroke
Cylinders	1	1
Valves per Cylinder	N/A	-
Capacity	420	229
Power (KW)	-	-
Torque (NM)	-	-
Gearbox	Automatic	ESP five-speed with Reverse and Automatic clutch
SAFETY		
Brakes	"(f) Dual hydraulic disc (r) Single hydraulic disc"	
STYLING		
Frame Material	Steel	Steel
WHEELS		
Tyres Front	24 x 8-12	22 x 7-11

Tyres Rear	24 x 10-11	22 x 10-9
Wheels	Steel	Steel

STANDARD AVAILABLE ACCESSORIES

Luggage	-	-
Maintenance	-	-
Comfort	-	-
Utility	-	-

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.