?

Models CRF250RX

CRF250RX 21YM

GENERAL

Warranty None

0 - 100 km/h (sec)

DIMENSIONS AND WEIGHTS

Claimed KERB Weight 101

Length (mm) 2185
Width (mm) 827
Height (mm) 1262
Seat height (mm) 960

Rake/Trail (°/mm) -

Wheel Base 1485

DRIVE

Drive Chain

Front Suspension 49mm Showa coil-sprung fork

Rear Suspension Showa monoshock using Honda Pro-Link system

ENGINE

Tank Capacity (l) 8.5

Starter Electric

Engine Configuration Liquid-cooled 4-stroke single DOHC

Cylinders 1 Valves per Cylinder 4

Capacity 249.4

Power (KW) Torque (NM) -

Gearbox 5-spd

SAFETY

Brakes (F)260mm hydraulic wave disc. (R)240mm hydraulic wave disc

STYLING

Frame Material Aluminium twin tube

WHEELS

Tyres Front 90/90-21 Dunlop AT81
Tyres Rear 110/100-18 Dunlop AT81
Wheels Aluminium rim/wire spoke

STANDARD AVAILABLE ACCESSORIES

Luggage Maintenance Comfort Utility -

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of

whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.