



Models CRF300L
CRF300L

GENERAL

Warranty 2 yrs
Service Intervals 12000 km
0 - 100 km/h (sec) -

DIMENSIONS AND WEIGHTS

Claimed KERB Weight 142
Length (mm) 2230
Width (mm) 820
Height (mm) 1200
Seat height (mm) 880
Rake/Trail (°/mm) 109
Wheel Base 1455

DRIVE

Drive Chain
Front Suspension 43mm telescopic USD fork
Rear Suspension Prolink

ENGINE

Tank Capacity (l) 7.8
Starter Electric
Engine Configuration Liquid-cooled, single cylinder DOHC
Cylinders 1
Valves per Cylinder 4
Capacity 286
Power (KW) 20.1kW/8500rpm
Torque (NM) 26.6Nm/6,500rpm
Gearbox 6-spd

SAFETY

Brakes 2 channel ABS (f) 256mm x 3.5mm disc with two piston caliper (r) 220 mm x 4.5mm disc with single piston caliper

STYLING

Frame Material Steel semi-double cradle

WHEELS

Tyres Front 80/100-21M/C 51P
Tyres Rear 120/80-18M/C 62P
Wheels Aluminium spoke

STANDARD AVAILABLE ACCESSORIES

- Luggage -
- Maintenance -
- Comfort -
- Utility -

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.