



Models XR150L
XR150L

GENERAL

Warranty 2 yrs
Service Intervals 4000 km
0 - 100 km/h (sec) -

DIMENSIONS AND WEIGHTS

Claimed KERB Weight 130
Length (mm) 2100
Width (mm) 810
Height (mm)
Seat height (mm)
Rake/Trail (°/mm) -
Wheel Base 1450

DRIVE

Drive Chain
Front Suspension 31mm telescopic fork, 160mm axle travel
Rear Suspension Single Shock, Single Tube, 150mm axle travel

ENGINE

Tank Capacity (l) 12
Starter Electric and Kick
Engine Configuration Air-cooled 4-stroke 2-valve OHV single
Cylinders 1
Valves per Cylinder 2
Capacity 149
Power (KW) 9.4kw / 7,750 r/min-1
Torque (NM) 13.0 Nm / 6,500 r/min-1
Gearbox 5-spd

SAFETY

Brakes (f) 240mm Hydraulic Disk (r) 110mm leading/trailing drum

STYLING

Frame Material Semi-Double Cradle; steel

WHEELS

Tyres Front 90/90-19
Tyres Rear 110/90-17
Wheels Wire Spoke Wheel

STANDARD AVAILABLE ACCESSORIES

Luggage -
Maintenance -
Comfort -
Utility -

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of

whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.